

DRAPER HEAD Specifications



Models 2142, 2152 & 2162

MODELS	2142	2152	2162
Description	Rigid Draper Header	Rigid Draper Header	Flexible Draper Header
CUTTER BAR			
Cutting Widths – ft. (m)	25, 30, 35 (7.6, 9.14, 10.6)	25, 30, 35, 40, 45 (7.62, 9.14, 10.6, 12.2, 13.7)	30, 35, 40 (9.14, 10.6, 12.2)
WEIGHT – APPROX. LBS (KG)			
25 ft. (7. m)	5,272 (2391)	5,596 (2538)	N/A
30 ft. (9.1 m)	5,967 (2706)	6,672 (2981)	6,648 (3015)
35 (10.6m)	6,444 (2923)	6,849 (3106)	7,061 (3202)
40 ft. (12.2 m)	N/A	7,285 (3282)	7,475 (3910)
AUGER			
Diameter – in. (mm)	Upper Cross – 12 (305) / Feed – 22 (356)	Upper Cross – 12 (305) / Feed – 22 (356)	Upper Cross – 12 (305) / Feed – 22 (356)
Speed – RPM	Cross – 0-464 / Feed – 150	Cross – 0-464 / Feed – 150	Cross – 0-464 / Feed – 150
REEL			
Pickup Reel (Tines)	5 bat plastic fingers, single span	5 or 6 bat plastic or steel fingers	5 or 6 bat plastic or steel fingers
Diameter – in. (mm)	65 (1651)	65 (1651)	65 (1651)
Drive – RPM	Hydraulic / 10 to 64 RPM	Hydraulic / 10 to 64 RPM	Hydraulic / 10 to 64 RPM
SICKLE/KNIFE			
Type	Overserrated, bolt sections	Overserrated, bolt sections	Overserrated, bolt sections
Drive	Enclosed oil bath wobble box	Enclosed oil bath wobble box	Enclosed oil bath wobble box
Knife - in. (mm)	3 (76.2)	3 (76.2)	3 (76.2)

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.



SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.